

AdVnce

PRODUCT Range

Forklifts • Pallet Trucks • Reach Trucks • Stackers • Order Pickers • VNA

COMFORT

SAFETY

EFFICIENCY



EUR region

TCM
Driven by Your Success

TCM AdVnce, the ultimate range combining TCM's world-class engineering DNA, robust manufacture, ultimate reliability, exceptional safety features and long-term performance. Built to excel in all environments, with advanced features and technology to make easy work of high intensity, multi-shift and complex, specialist applications. Designed to be long lasting, with high return.



SAFETY

INTEGRAL TO OUR TRUCKS FOR SAFER OPERATIONS

- Stability support systems built in as standard.
- Safety is not just a feature, it's integral to our design ethos, prioritising safer working environments with reduced accidents.
- In-built security functions to prevent unauthorised operation.
- Engineered for 360° degree visibility.
- Our flexible control systems allow you to optimise the safety features for your applications.



ADVANCED TECHNOLOGY

CUSTOMISE TO ANY APPLICATION

FEATURE RICH

HIGH PERFORMANCE

LOW TCO TOTAL COST OF OWNERSHIP

TCM Dealer Network

All AdVNCE models are backed up by our excellent Global Service & Support Network



COMFORT

CONSIDERING THE OPERATOR TO INCREASE PRODUCTIVITY

- Utilising the science behind ergonomics to create a truck that works with the operator.
- Operator areas with exceptional functionality and easy access in mind.
- Feature rich, designed to minimise your total cost of operation.
- We understand working environments to ena.



EFFICIENCY

INDUSTRY LEADING PERFORMANCE UTILISING NEW TECHNOLOGIES

- Low fuel and power consumption.
- Easy servicing and maintenance, minimising your downtime.
- Eco-modes to save energy.
- High efficiency, low maintenance lithium battery options.



Li-ION

LONGER LIFE

HIGHER EFFICIENCY

LONGER RUNTIME

CONSISTENT PERFORMANCE

FASTER CHARGING

NO MAINTENANCE

INBUILT PROTECTION

Lithium-ion batteries can offer real advantages over lead-acid batteries, particularly in high energy, multi-shift, and 24/7 applications. When it comes to Total Cost of Ownership (TCO), TCM can advise you on the most cost-effective energy solution you will need to meet all your operational requirements.

Like every TCM solution, Li-ion batteries are engineered for ultimate reliability and high performance even in the toughest environments. We simplify procurement, servicing, and warranty claims by keeping everything under one trusted brand, TCM.



Electric Counterbalance Forklift Trucks

AdVnce

FTB1.4-2.0

3 WHEEL 48 VOLT COUNTERBALANCE TRUCK
LIFT CAPACITY 1400/1600/1800/2000 kg
LIFT HEIGHT Up to 7 metres



FB1.6-2.0

4 WHEEL 48 VOLT COUNTERBALANCE TRUCK
LIFT CAPACITY 1600/1800/2000 kg
LIFT HEIGHT Up to 7 metres



FHB4.0-5.5

4 WHEEL 80 VOLT COUNTERBALANCE TRUCK
LIFT CAPACITY
4000/4500/5000/5500 kg
LIFT HEIGHT
Up to 7 metres



FHB2.5-3.5

4 WHEEL 80 VOLT COUNTERBALANCE TRUCK
LIFT CAPACITY
2500/3000/3500 kg
LIFT HEIGHT
Up to 7 metres



FHB6.0-12.0

4 WHEEL 96 VOLT COUNTERBALANCE TRUCK
LIFT CAPACITY
6000/6500/7000/8000/9000
10000/12000 kg
LIFT HEIGHT
Up to 6.1 metres



Diesel/LPG Counterbalance Forklift Trucks



FD/FGE1.5-3.5

ENGINE COUNTERBALANCE TRUCK

DIESEL LIFT CAPACITY 2000/2500/3000/3500 kg

LPG LIFT CAPACITY 1500/1750/2000/2500/3000/3500 kg

Diesel/LPG

LIFT HEIGHT

Up to 7 metres



FD/FGE4.0-5.5

ENGINE COUNTERBALANCE TRUCK

DIESEL LIFT CAPACITY 2000/2500/3000/3500 kg

LPG LIFT CAPACITY 1500/1750/2000/2500/3000/3500 kg

Diesel/LPG

LIFT HEIGHT

Up to 7 metres



FD6.0-10.0

ENGINE COUNTERBALANCE TRUCK

LIFT CAPACITY 6000/7000/8000/10000 kg

Diesel only

LIFT HEIGHTS

Up to 8 metres



Pallet Trucks

TE/TV
PEDESTRIAN HAND
PALLET TRUCK

LIFT CAPACITY
2500 kg



PAL
COMPACT PEDESTRIAN
PALLET TRUCK WITH
OR WITHOUT FOLDABLE
PLATFORM

LIFT CAPACITY
1600/1800/2000 kg



PTF
PEDESTRIAN PALLET TRUCK
WITH RIDER PLATFORM

LIFT CAPACITY
2000/2500 kg



PTP
PEDESTRIAN PALLET
TRUCK WITH PROTECTED
PLATFORM. SIDE OR
REAR ENTRY

LIFT CAPACITY
2000/2500 kg



LLR
STAND-IN PALLET TRUCK

LIFT CAPACITY
2000/3000 kg



LLS
SIT-ON PALLET TRUCK

LIFT CAPACITY
2000/3000 kg



Reach Trucks

RTL/RTN
NARROW CHASSIS
REACH TRUCK

LIFT CAPACITY
1200/1400 kg
LIFT HEIGHT
Up to 8.95 metres



RTM/RTH/RTX
REACH TRUCK

LIFT CAPACITY
1600/2000/2500 kg
LIFT HEIGHT
Up to 12.1 metres



RTM-TF/RTH-TF
REACH TRUCK WITH TELESCOPIC FORKS

LIFT CAPACITY 2000/2500 kg
LIFT HEIGHT Up to 10.2 metres



RTF
4 - WAY REACH TRUCK

LIFT CAPACITY
2000/2500 kg
LIFT HEIGHT
Up to 9.7 metres



AdVnce



Stackers

SPW/SPR

COMPACT PEDESTRIAN
STACKER WITH OR
WITHOUT FOLDABLE
PLATFORM

LIFT CAPACITY
1000/1200
1400/1600 kg

LIFT HEIGHT
Up to 5.4 metres



SRD

RIDE-ON DOUBLE PALLET STACKER
WITH FOLDABLE PLATFORM, OR
SIDE OR REAR ENTRY
FIXED PLATFORM

LIFT CAPACITY
2000 kg

LIFT HEIGHT
2.1 metres



SRO

STAND-IN STACKER,
STANDARD OR WIDE
STRADDLE

LIFT CAPACITY
1250/1600/2000 kg

LIFT HEIGHT
Up to 7 metres



SSO

SIT-ON STACKER,
STANDARD OR
WIDE STRADDLE

LIFT CAPACITY
1600/2000 kg

LIFT HEIGHT
Up to 7 metres



SRS

RIDE-ON PEDESTRIAN
STACKER WITH FOLDABLE
PLATFORM, OR SIDE
OR REAR ENTRY FIXED
PLATFORM

LIFT CAPACITY
1250/1600 kg

LIFT HEIGHT
Up to 5.4 metres



SRT/SST

STAND-IN AND SIT-ON
STACKER WITH
TELESCOPIC FORKS

LIFT CAPACITY
1200 kg

LIFT HEIGHT
Up to 6.3 metres



Order Pickers

HIGH-LEVEL ORDER PICKER

EOC

LIFT CAPACITY
1000 kg

LIFT HEIGHT
Up to 8.25 metres



EOH

LIFT CAPACITY
1250 kg

LIFT HEIGHT
Up to 10.5 metres



MEDIUM-LEVEL ORDER PICKER

EOM

LIFT CAPACITY
1000 kg

LIFT HEIGHT
Up to
1.8 metres



LOW-LEVEL ORDER PICKER

LO

WITH STANDARD OR RISING
PLATFORM WITH OR WITHOUT
RISING FORKS

LIFT CAPACITY
1200/2000/2500 kg

LIFT HEIGHT
220/850 mm

PLATFORM HEIGHT
123/1000 mm



Very Narrow Aisle Trucks

RTS

MAN-DOWN VNA TRUCK

LIFT CAPACITY
1250/1500 kg

LIFT HEIGHT
Up to 10.35 metres



VTU

MAN-UP VNA TRUCK

LIFT CAPACITY
1100/1200/1300/1350/
1500/2000 kg

LIFT HEIGHT
Up to
19 metres



AdVnce

Ultimate Precision, Power and Performance



TCM

Driven by Your Success

tcm.eu

© 2026 Logisnext Europe B.V. All rights reserved. Specifications are indicative and may vary depending on operating conditions. Failure to assess all factors may result in performance deviations. All relevant sales support materials and technical expertise of the official distributor must be considered when identifying the best product/solution. Options and technical details may change without notice. See full legal notices and up-to-date product information at www.tcm.eu AEBT2656-0426